

PRB SR ADDITIF

LIQUID DRYING ACCELERATOR FOR PRE-MIXED FINISHING PRODUCTS

Benefits of the PRB SR ADDITIF

-  Speeds up the initial setting time of thin coat pre-mixed, ready to use finishes, paints and **PRB FONDISOL PE**, forming an early surface film
-  Ideal for wet, damp and cold weather
-  Ready to use

KEY PRODUCT INFORMATION

- Box of 30 recycled plastic 250 ml containers.

STORAGE: 12 months

CONSUMPTION: 1 dose of 250 ml per one 17 to 25 kg bucket

COLOUR: From clear to slightly yellow.

**UK
CA**



TECHNICAL

PRODUCT CHARACTERISTICS

- Appearance: Liquid
- Colour: From clear to slightly yellow
- Density: 1.05 ± 0.05
- pH: 10.5 ± 0.5

APPLICATION REQUIREMENTS

After the addition of **PRB SR ADDITIF**, it is essential to quickly mix the whole product added to using a paddle mixer at a maximum speed of 300 rpm. Ensure the product is fully mixed before using. To avoid shade differences, ensure the accelerator is added equally to all tubs on the same elevation.

Technical sheet - June 2026

The only purpose of this technical data sheet is to inform customers about the product and its specific uses. The information it contains is based on current knowledge and experience. The end user must carry out a representative test to ensure the product is suitable for their specific application and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors. Our general terms and conditions of sale shall prevail, and the end user should check to ensure this document has not been replaced by a more updated version.

 01242 524228

 technical@prbsystems.co.uk

 www.prbsystems.co.uk

 Montis Court, Bouncers Lane, Cheltenham, GL52 5JW