

PRB ORANGE MESH

MESH FOR PRB RENDERS (SUPERBRUT, OZÉ, SC GRIS, THERMOLOOK etc)

Benefits of the PRB ORANGE MESH



- + Coated glass fibre reinforcement mesh
- + Specially designed for monocouche renders
- + Compatible with PRB floor levellers

KEY PRODUCT INFORMATION

- 1 m x 50m rolls
- 20 rolls per euro pallet

**UK
CA**



CONSUMPTION: 45m² per roll @ 0.9m² includes for a 100 mm overlap

STORAGE: Store vertically. Packed rolls are to be stored in dry conditions. Avoid storing in direct sun for a long period of time. Storing temperature is from -10°C to + 50°C.



USAGE GUIDE

WHERE TO USE?

- Exterior walls.
- Interior floors.

PRB ORANGE MESH is used as a reinforcement for the PRB mineral one coat (monocouche), topcoat and basecoat renders. Suitable for incorporating as stress patches around openings and as full mesh applications. It can also be used for a wide range of repair applications and for applications in screeds and floor levelling solutions. A high quality synthetic coating on the glass yarn protects the mesh against alkaline influences from the renders and basecoat materials that are used.

TECHNICAL

PRODUCT CHARACTERISTICS

- **Type:** Woven mesh.
- **Weft direction:** 8 ± 0.5 mm
- **Weave direction:** 8 ± 0.5 mm
- **Density:** 200 ± 10 % g/m²
- **Tensile strength – Warp / Weft:**
44 / 67 N/mm
- **After 5% NaOH solution – Warp / Weft:** 23 / 34 N/mm

Technical sheet – June 2026

PRODUCT COMPOSITION

NATURE OF THE COMPONENTS:

- **Thread:** Fibreglass.
- **Coating resin:** Specially designed surface treatments.

PRODUCT IDENTIFICATION

- **Standard colour:** Orange with the PRB logo printed throughout the length of the mesh
- **Marking:** A printed line 100 mm from the edge to provide overlap guidance.

The only purpose of this technical data sheet is to inform customers about the product and its specific uses. The information it contains is based on current knowledge and experience. The end user must carry out a representative test to ensure the product is suitable for their specific application and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors. Our general terms and conditions of sale shall prevail, and the end user should check to ensure this document has not been replaced by a more updated version.

01242 524228

technical@prbsystems.co.uk

www.prbsystems.co.uk

Montis Court, Bouncers Lane, Cheltenham, GL52 5JW