

PRB LOW TACK RENDER TAPE

LOW TACK RENDER TAPE

Benefits of the PRB LOW TACK RENDER TAPE +

- + Ideally suited for bonding to window frames & smooth surfaces
- + Excellent adhesion to surfaces
- + Clean & easy removal
- + Waterproof

STANDARD SIZE: Width 48mm x Length 50m

COLOUR: White



USAGE GUIDE

TYPICAL APPLICATIONS

- **PRB LOW TACK RENDER TAPE** is suitable for applications onto smooth surfaces, e.g. window and door frames, metalwork, paint or smooth masonry finishes e.g plaster. It is easy to tear and provides a durable, water resistance, and protective surface over areas that need to be kept clean. The special adhesive is designed to prevent any residue being left behind once the tape is removed, however performance may vary depending upon the temperatures on-site. E.g. Cold and freezing temperatures could cause a lack of adhesion and high temperatures could result in left-over adhesive residue. Prior to use test the tape onto a discreet location.

TECHNICAL CHARACTERISTICS

PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	140	my	(+/- 10 %)
Adhesion to Stainless Steel @ 180	≥ 10	N/2.5cm	-
Adhesion to cured paint on drywall	8	N/2.5cm	-
Service Temperature Range	- 5 to + 60	° C	-

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area (not more than 21°C and 50% relative humidity), away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

Technical sheet - April 2025

The only purpose of this technical data sheet is to inform customers about the product and its specific uses. The information it contains is based on current knowledge and experience. The end user must carry out a representative test to ensure the product is suitable for their specific application and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors. Our general terms and conditions of sale shall prevail, and the end user should check to ensure this document has not been replaced by a more updated version.

01242 524228

technical@prbsystems.co.uk

www.prbsystems.co.uk

Montis Court, Bouncers Lane, Cheltenham, GL52 5JW

PRB RENDER / BRICK TAPE

EXTERIOR RENDER / BRICK TAPE

Benefits of the PRB RENDER / BRICK TAPE +

- + Strong bond & suitable for rough surfaces
- + Excellent adhesion to surfaces
- + Clean & easy removal
- + Waterproof
- + **STANDARD SIZE: Width 48mm x Length 50m**
COLOUR: Orange



USAGE GUIDE

TYPICAL APPLICATIONS

- **PRB RENDER / BRICK TAPE** is suitable for applications onto rough surfaces, brick, concrete blocks etc. It is easy to tear and provides a durable, water resistant and protective surface over areas that need to be kept clean. The special adhesive is designed to prevent any residue being left behind once the tape is removed, however performance may vary depending upon the temperatures on site. E.g. Cold and freezing temperatures could cause a lack of adhesion and high temperatures could result in left-over adhesive residue. Prior to using we suggest testing the tape onto a discreet location.

TECHNICAL CHARACTERISTICS

PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	200	my	(+/- 15 %)
Adhesion to Stainless Steel @ 180	≥ 15	N/2.5cm	-
Tensile strength	30	N/2.5cm	(+/- 5 %)
Service Temperature Range	from - 5 to + 60	° C	-
	from 23 to 140	° F	-

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area (not more than 21°C (70°F) and 50% relative humidity) away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

Technical sheet - April 2025

The only purpose of this technical data sheet is to inform customers about the product and its specific uses. The information it contains is based on current knowledge and experience. The end user must carry out a representative test to ensure the product is suitable for their specific application and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors. Our general terms and conditions of sale shall prevail, and the end user should check to ensure this document has not been replaced by a more updated version.

01242 524228

technical@prbsystems.co.uk

www.prbsystems.co.uk

Montis Court, Bouncers Lane, Cheltenham, GL52 5JW

PRB ROUGH SURFACE RENDER TAPE

EXTERIOR ROUGH SURFACE RENDER TAPE

Benefits of the PRB ROUGH SURFACE RENDER TAPE +

- + Suitable for rough surfaces
- + Excellent adhesion to surfaces
- + Clean & easy removal
- + Waterproof
- + **STANDARD SIZE: Width 48mm x Length 50m**
COLOUR: White



USAGE GUIDE

TYPICAL APPLICATIONS

- **PRB ROUGH SURFACE RENDER TAPE** is suitable for applications onto rough surfaces, brick, existing render, concrete block, etc. It is easy to tear and provides a durable, water resistant and protective surface over areas that need to be kept clean. The special adhesive is designed to prevent any residue being left behind once the tape is removed, however performance may vary depending upon the temperatures on site. E.g. Cold and freezing temperatures could cause a lack of adhesion and high temperatures could result in left-over adhesive residue. Prior to using we suggest testing the tape onto a discreet location.

TECHNICAL CHARACTERISTICS

PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	200	my	(+/- 15 %)
Adhesion to Stainless Steel @ 180	≥ 15	N/2.5cm	-
Tensile strength	30	N/2.5cm	(+/- 5 %)
Service Temperature Range	from - 5 to + 60	° C	-
	from 23 to 140	° F	-

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area (not more than 21°C (70°F) and 50% relative humidity) away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

Technical sheet - April 2025

The only purpose of this technical data sheet is to inform customers about the product and its specific uses. The information it contains is based on current knowledge and experience. The end user must carry out a representative test to ensure the product is suitable for their specific application and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors. Our general terms and conditions of sale shall prevail, and the end user should check to ensure this document has not been replaced by a more updated version.

01242 524228

technical@prbsystems.co.uk

www.prbsystems.co.uk

Montis Court, Bouncers Lane, Cheltenham, GL52 5JW